

MANUAL GRAVITY SLICER BELT DRIVEN

Model
START 300/350

Large clearance between blade and base.
High protection against moisture

Carriage smooth glide motion

Powerful and noiseless motor

Sturdy construction for precise slices

Wide slice exit area with no-drip profile

Thickness adjustment: gasket-sealed mechanism



AVAILABLE CONFIGURATIONS

ANODYZED



All external aluminium parts are silver anodized: *TRADITIONAL SILVER FINISHING.*

BASIC QUANTANIUM



Gauge plate, blade and blade cover disc are non-stick coated. Remaining aluminium parts are anodized: *CHEESE CUTTING IS NO MORE A PROBLEM.*

TOTAL QUANTANIUM



All external aluminium parts are black Quantanium non-stick coated to be resistant to all detergents: *THE BLACK APPEAL.*

STANDARD OUTFIT



User Manual, CE compliance declaration and "TEN BASIC RULES" Cardboard.



FAST CLEANER detergent, Cleaning nylon brush, Oiler.



Quantanium® with Titanium particles reinforced three-layer non-stick coating will allow:
● smoothness: difficult products

like cheese or fresh meat do not stick and products slide smoothly and frictionless;

- higher resistance to abrasion;
- resistance to most aggressive detergents.

AVAILABLE OPTIONS



SBR (Safe Blade Removal): it allows for quick and safe removal of the blade during slicer cleaning.



Non stick coated blade, perfect for cheese and fish cutting. Already included in Quantanium® configuration.



Serrated blade for frozen food cutting.



Stainless steel chute for vegetable cutting.





Inclined product holder. Easy to assemble, no tools needed.



ES (Energy saver): drastically reduces power consumption.

DIMENSIONS



SPECIFICATIONS AND SHIPPING INFORMATION

| Model name | Blade mm | Power Hp/kW | Drive | Cut Capacity mm | Cut thick. mm | Net weight kg |
|------------------|----------|-------------|-------|-----------------|---------------|---------------|
| START 300 | 300 | 0,35/0,25 | Belt | 240x160 ○ 190 | 20 | 29 |
| START 350 | 350 | 0,35/0,25 | Belt | 280x190 ○ 220 | 20 | 32 |

All voltages and frequencies are available on request.

SHIPPING

| Dimension | Weight |
|-----------------|--------|
| cm 74 x 58 x 56 | 35 kg |
| cm 79 x 64 x 58 | 39 kg |